



FEATURES

- RoHS compliant, UL94V-0
- Small size (5.75*5.4mm Max), low profile (Height: 3.0mm Max)
- Inductance range from 0.10uH to 15.0uH
- Surface mount design
- Magnetic shield construction
- Ultra low buzz noise due to composite construction
- Handle transient current spikes without saturation
- Tape & reel packing
- Solder profile acc. J-STD-020D

APPLICATIONS

- Low profile, high current power supplies
- DC/DC converters
- Battery powered devices
- PDA/notebook/desktop/server applications

Part number	Inductance (μ H \pm 20%)	DCR TYP. (m Ω)	DCR MAX. (m Ω)	I _{rms} (A)	I _{sat} (A)
MHC0530SGR10M	0.10	3.00	3.16	23.0	27.0
MHC0530SGR22M	0.22	4.30	4.52	15.5	21.0
MHC0530SGR33M	0.33	5.30	5.56	13.7	19.0
MHC0530SGR47M	0.47	6.70	7.04	12.2	16.0
MHC0530SGR68M	0.68	8.53	8.96	10.2	13.5
MHC0530SGR82M	0.82	11.3	11.9	9.3	13.0
MHC0530SG1R0M	1.0	13.1	13.7	9.2	12.0
MHC0530SG1R5M	1.5	19.7	20.7	7.2	11.0
MHC0530SG2R2M	2.2	27.8	29.2	5.8	10.0
MHC0530SG3R3M	3.3	52.1	54.7	5.0	8.5
MHC0530SG4R7M	4.7	73.8	77.5	3.5	8.2
MHC0530SG5R6M	5.6	103.0	108.0	3.0	4.1
MHC0530SG100M	10.0	158.0	164.0	2.5	4.0
MHC0530SG150M	15.0	252.0	265.0	1.9	2.5



ABSOLUTE MAXIMUM RATINGS

Operating temperature rang (Including coil' self temperature rise)	-55°C to +125°C
Storage temperature rang	-55°C to +125°C

SOLDERING INFORMATION

Peak reflow temperature	250°C
Pin finish	tin

PACKAGING INFORMATION

Tape&Reel	2000pcs per reel
Weight	0.44g/pcs

Notes

1. Electrical specification at 25°C.
2. Inductance tested at 100 kHz, 0.25Vrms.
3. I_{rms} is the current that caused a approximate 40°C temperature rise from 25°C ambient.
4. I_{sat} is the DC current at which inductance drop approximately 20% from its value without current.
5. The part temperature(ambient + temp.rise) should not exceed 125°C under worst case operating conditions. Circuit design, component placement, PWB trace size and thickness, airflow and other cooling provisions all affect the part temperature. Part temperature should be verified in the end application.